



## Vetotop CS537

Premixed 20 to 100 mm thick cementitious bonded screed

### Uses

- Leveling of concrete slabs prior to the application of final floor coverings.
- Screeding over hollow-core pre-cast concrete slabs.

### Product Description

Vetotop CS537 is a single component cementitious bonded floor screed composed of hydraulic binders, silica sand, selected aggregates, and special additives. It is supplied as a dry powder in pre-weighed bags ready to use on-site. Once mixed, it will form a trowelable screed mortar applied in thicknesses between 20 and 100 mm.

### Advantages

- Factory-controlled pre-blend ensures consistently high quality.
- Suitable for Middle East harsh weather conditions.
- Easy application enabling high productivity & superior finishing.
- High bond to the substrate.
- Excellent physical and mechanical properties.
- Shrinkage compensated.
- Excellent workability.

### Technical Data

Vetotop CS537	Typical Values
Appearance	Granular Grey
Aggregate size (mm)	0 - 5
Application Thickness (mm)	20 - 100
Dry Density (Kg/L)	1.7 ± 0.1 Approx.
Wet Density (Kg/L)	2.3 ± 0.1
Working Time @ 25°C (Minutes)	30 Approx.
Compressive Strength - EN 13892-2 @ 28 Days (N/mm <sup>2</sup> )	> 33
Flexural Strength - EN 13892-2 @ 28 Days (N/mm <sup>2</sup> )	> 5.5
Wear Resistance to Rolling Wheel - EN 13892-5 (cm <sup>3</sup> )	≤ 100
Bond Strength - EN 13892-8 (N/mm <sup>2</sup> )	≥ 1.0
Setting Time - EN 13454-2 (Hours)	3.5 - 4.5
Water Demand (%)	9 - 10

### Standards Compliance

- EN13813 CT - C30 - F5 - B1.0 - RWA100

## Usage Instructions

### Surface Preparation

The surface should be sound, clean, free from loose material, grease, laitance, dirt curing compound, etc.

### Priming

Vetotop CS537 is a bonded screed that can be laid in thickness between 20 - 100 mm.

An epoxy bonding agent can be used for more adhesion, such as Vetobond EB430 or Vetobond EB431. Vetobond PB434 slurry can also be used.

To prepare the slurry primer, mix 1 volume of Vetobond PB434 to 1 volume of clean water with 3 volumes of fresh cement and mix until a smooth consistency is achieved. Scrub the mixed slurry into the concrete surface; while the slurry is wet, apply Vetotop CS537 to ensure good adhesion with the substrate.

### Mixing

For mixture preparation, pour into a container 4.5-5 liters of water for 50 Kg bag of Vetotop CS537.

Add the powder to the water and mix with a low-speed electric drill fitted with a suitable paddle until a uniform, lump-free consistency mix is achieved. Do not add further water to the mix. Do not add water to the mix once it starts to set.

### Application

Pour the mixed product onto the surface and spread to the desired thickness using a steel trowel or suitable tools. Cover the surface with a plastic sheet to avoid drying.

### Curing

Cure the screed as per standard concrete curing practices. Do not subject the screed to vehicular traffic for 28 days till ensuring full cure and the system's ability to withstand designed traffic loads.

A concrete sealer is required for enhancing the screed durability and resistance to ingress of water. Apply Vetoseal XW770 at a rate of 8 to 12 m<sup>2</sup> per liter. Make sure that the sealer is uniformly applied and covering all screed surfaces.

### Legal Disclaimer

Saveto endeavors to ensure that any advice, recommendations, information it may give is accurate and correct. It cannot accept any liability either directly or indirectly arising from the use of its products because it has no direct or continuous control over where or how its products are applied, whether or not following any advice, specification, recommendation, or information given by us. Saveto has the right to change any of the technical datasheets specifications upon its discretion without prior notification.

Hard copies of TDSs are printed once or twice a year. Our technical data sheets are continuously updated as per R&D improvements and new 3rd party testing; kindly refer to our website for the latest updated TDSs.

### Cleaning

Clean tools with water promptly before material hardens. Hardened material can be mechanically removed.

### Packaging & Coverage

Product	Pack Size	Yield
Vetotop CS537	50 kg Bag	23.5 Liters Approx.

Stated consumption data are for general guidance. Actual consumption depends on the nature of substrate, method of application, and wastage.

### Shelf Life & Storage

The original sealed bag of Vetotop CS537 has a shelf life of 12 months, provided it is stored clear of ground in a dry and shaded place below 35°C.

### Limitations

- Do not apply the product at a temperature of less than +5°C.
- Vetotop CS537 should be checked for its suitability when concrete is steam cured. Also, carry out prior tests for its suitability when gypsum or colored mixes are being used.
- For further information contact our technical department.

### Health & Safety

Vetotop CS537 is highly alkaline; therefore, avoid direct contact with eyes or skin. Vetobond PB434 is a latex emulsion. It is recommended to use protective gloves and goggles during application.

Any skin contact should be washed with plenty amount of water. In case of eye irritation, immediately wash with a copious amount of clean cold water. Seek medical advice.

Vetotop CS537 is non-flammable.

### Additional Information

Saveto manufactures a wide range of construction chemicals and specialty products for various applications.

For further information on these products and systems kindly check our website or contact your local Saveto representative.