



## Vetotouch Décor FB

Fine finish textured decorative coating, flexible, ready-to-use, and based on acrylic emulsion

### Uses

- Used as a heavy textured decorative coating for interior and exterior surfaces, such as concrete, cement, bricks, plaster, prefabs, gypsum board, masonry work, steel, and galvanized steel surfaces.
- Suitable for application on wooden surfaces.
- Ideal for use in educational institutions, residential, commercial, and industrial buildings, prefabs, boundary walls, etc.

### Product Description

Vetotouch Décor FB (Fine Build) is a single-component, excellent texture topcoat profile that resists all weather conditions. Vetotouch Décor FB is a high-quality product suitable for internal and external applications. It is designed to provide a matt finish with a fine-build texture.

### Advantages

- Easy to apply.
- UV-resistant.
- Highly durable.
- Enhance the thermal insulation as a system.
- Excellent resistance to weather conditions.
- Good water resistance to prevent penetration of dampness on exterior walls.
- Can be formed into different rough texture designs using a roller, brush, or spray gun.

### Technical Data

Vetotouch Décor FB	Typical Values @ 25°C, 50% RH
Finish	Matt, rough fine texture
Tack Free Time (Hours)	1 - 2
Density (kg/ltr)	1.64
Drying Time (Hours)	3 - 4
Solid Content (By weight%)	82
Over Coating Time (Hours)	6 - 8
Application Temperature (°C)	5 to 40
Full Dry Time (Days)	7

## Usage Instructions

### Surface Preparation

All new concrete surfaces must be cured for at least 28 days prior to the application of the primer.

For previously painted surfaces, remove old paint completely. The substrate should have sufficient strength and be free from unsound areas, pug holes, protrusions, and pops.

Ensure that the surface is clean, dry, and free from dust, oil, grease, salt, mold, and all forms of release agents/curing agents. A light sanding with suitable abrasive material is recommended before application. Any resulting dust or loose particles must be removed before application.

### Priming

Priming is not required for good quality non-porous concrete. However, if the concrete surface is porous or if there is any doubt about the quality of the concrete surface, use Vetoprime Décor.

Apply one coat of Vetoprime Décor for both exterior and interior applications and allow it to completely dry before proceeding.

### Mixing

Stir well before use with a flat paddle to achieve a homogeneous consistency. Stir occasionally during use. Additives are not permitted. Close the container when not in use.

### Application

Apply and level Vetotouch Décor FB using a roller, brush, or spray gun during the same operation to achieve the minimum obtainable thickness consistent with uniform coverage.

### Cleaning

Remove Vetotouch Décor FB from tools, equipment, and mixers with clean water before the initial set. Cured material can only be removed mechanically.

### Legal Disclaimer

Saveto endeavors to ensure that any advice, recommendations, information it may give is accurate and correct. It cannot accept any liability either directly or indirectly arising from the use of its products because it has no direct or continuous control over where or how its products are applied, whether or not following any advice, specification, recommendation, or information given by us. Saveto has the right to change any of the technical datasheets specifications upon its discretion without prior notification.

Hard copies of TDSs are printed once or twice a year. Our technical data sheets are continuously updated as per R&D improvements and new 3rd party testing; kindly refer to our website for the latest updated TDSs.

## Packaging & Coverage

Product	Pack Size	Coverage
Vetotouch Décor FB	16 Liter	0.4 m <sup>2</sup> /liter/coat @ 2 mm thickness

Stated consumption data are for general guidance. Actual consumption depends on the nature of the substrate, consistency used, method of application, and wastage.

### Shelf Life & Storage

The original sealed container of Vetotouch Décor FB has a shelf life of 12 months, provided it is stored clear of ground in a dry and shaded place below 35°C.

### Limitations

Do not apply Vetotouch Décor FB on wet and moistened surfaces until completely dry.

Do not apply the next coat unless the previous one is fully dry.

Cannot be applied to bare, un-primed metal and over coated with non-flexible paints.

### Health & Safety

Vetotouch Décor FB and Vetoprime Décor contain an acrylic polymer that can be harmful to the skin. During use, avoid contact with skin and eyes. Wear suitable protective clothing, gloves, eye protection, and respiratory protective equipment. The use of barrier cream provides additional skin protection.

In case of skin contact, rinse with plenty of clean water, then cleanse with soap and water. In case of eye contact, rinse immediately with plenty of clean water and seek medical advice. If swallowed, seek medical attention immediately—do not induce vomiting.

Vetotouch Décor FB and Vetoprime Décor are non-flammable.

### Additional Information

Saveto manufactures a wide range of construction chemicals and specialty products for various applications.

For further information on these products and systems kindly check our website or contact your local Saveto representative.