

BONDING AGENTS AND PRIMERS



Vetoprime Décor

Single-component, general-purpose, PVA-based primer

Uses

- Designed to prime surfaces prior to the application of Vetotouch Décor.
- Suitable for porous and slightly chalky surfaces.
- Suitable for interior and exterior use on concrete, masonry, plaster, asbestos, gypsum, and brickwork, etc.

Product Description

Vetoprime Décor is a single-component, general-purpose, PVA-based emulsion sealer with excellent penetration and sealing properties for cementitious surfaces, featuring excellent adhesion, moderate alkali resistance, and containing anti-fungal and anti-bacterial additives, making it suitable for both interior and exterior masonry applications, while also being specially formulated as a penetrating primer for masonry surfaces, particularly for use in texture systems.

Advantages

- Easy to apply.
- Excellent adhesion.
- Moderate alkali resistance.
- Odor free and non-flammable.
- Environmentally friendly.
- Excellent penetration and sealing property.

Technical Data

Vetoprime Décor	Typical Values @ 25°C, 50% RH
Color	White
Finish	Smooth / Matt
Touch Dry Time (Hours)	1
Density (kg/liter)	1.36
Solid Content (by weight%)	49
Chloride Content	Nil
Over Coating Time (Hours)	2 - 3
Application Temperature (°C)	5 to 40
Thinning (Volume%)	10 - 15
Thinning / Cleaner	Water



BONDING AGENTS AND PRIMERS

Usage Instructions

Surface Preparation

All new concrete surfaces must be cured at least for 28 days prior to application of the primer.

For previously painted surfaces remove old paint completely. The substrate should have sufficient strength and free from unsounded areas, pug holes, protrusions, and pops.

Make sure that the surface is clean, dry, free from dust, oil, grease, salt, mold and all forms of release agents /curing agents must be removed. A light sanding with suitable abrasive material is recommended before application. Any resulting dust/loose particles must be removed before application.

Mixing

Stir well before use with a flat paddle to a homogenous consistency. Stir occasionally during use. Additives are not permitted. Close container when not in use.

Application

Apply 1-2 coats of Vetoprime Décor by a roller, brush, or a spray gun and allow it completely dry.

Cleaning

Remove Vetoprime Décor product from tools, equipment, and mixers with clean water before the initial set. Cured material can only be removed mechanically.

Packaging & Coverage

Product	Pack Size	Coverage
Vetoprime Décor	15 Liter	4.9 m²/liter/coat @ 100 micron thickness

Stated consumption data are for general guidance. Actual consumption depends on the nature of the substrate, consistency used, method of application, and wastage.

Shelf Life & Storage

The original sealed container of Vetoprime Décor has a shelf life of 18 months, provided it is stored clear of ground in a dry and shaded place below 35 °C.

Limitations

- Vetoprime Décor should not be applied at ambient temperature below 5 °C.
- Do not apply Vetoprime Décor on wet and moistened surfaces until completely dry.
- Do not apply the next coat unless the previous one is fully dry.
- For further information contact our technical department.

Health & Safety

Vetoprime Décor contains an acrylic polymer that can be harmful to the skin. During use, avoid contact with skin and eyes. Wear suitable protective clothing, gloves, eye protection, and respiratory protective equipment. The use of barrier cream provides additional skin protection. In case of skin contact, rinse with plenty of clean water, then cleanse with soap and water. In case of contact with the eye, rinse immediately with plenty of clean water and seek medical advice. If swallowed, seek medical attention immediately – do not induce vomiting.

Vetoprime Décor is non-flammable.

Refer to product MSDS for further information.

Additional Information

Saveto manufactures a wide range of construction chemicals and specialty products for various applications.

For further information on these products and systems kindly check our website or contact your local Saveto representative.

Legal Disclaimer

Saveto endeavors to ensure that any advice, recommendations, information it may give is accurate and correct. It cannot accept any liability either directly or indirectly arising from the use of its products because it has no direct or continuous control over where or how its products are applied, whether or not following any advice, specification, recommendation, or information given by us. Saveto has the right to change any of the technical datasheets specifications upon its discretion without prior notification.

Hard copies of TDSs are printed once or twice a year. Our technical data sheets are continuously updated as per R&D improvements and new 3rd party testing; kindly refer to our website for the latest updated TDSs.

Ref No.: G06-P23-V01-24 SA www.saveto.com